

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization International Bureau



(43) International Publication Date
17 February 2005 (17.02.2005)

PCT

(10) International Publication Number
WO 2005/015519 A1

(51) International Patent Classification⁷: **G08C 17/02**

(74) Agents: ATKINSON, Ralph et al.; Atkinson Burrington, 28 President Buildings, President Way, Sheffield S4 7UR (GB).

(21) International Application Number:
PCT/GB2004/003427

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(22) International Filing Date: 6 August 2004 (06.08.2004)

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(25) Filing Language: English

(26) Publication Language: English


(30) Priority Data:
0318380.3 6 August 2003 (06.08.2003) GB

Published:

— with international search report

[Continued on next page]

(54) Title: REMOTE CONTROL SYSTEM FOR CONTROLLING APPARATUS IN RESPONSE TO A VARIABLE



(57) Abstract: A hotel floor (110) comprises rooms (112) each provided with a central heating radiator (114) having a valve (114a) adjustable by means of a 0-10V dc stepper motor (114b). In the hotel lobby (116) a sensor (122) for ambient temperature is connected to a radio transmitter (120) and radio receivers (114c) are connected to the stepper motors (114b) in each room (112). If the ambient temperature falls, the transmitter (120) transmits to the receivers (114c) a signal representing the lower temperature, and the stepper motors (114b) open the valves (114a). If the temperature rises, the transmitter (120) transmits another signal, and the stepper motors 114b close the valves (114a). Thus the heat output of the radiators (114) is varied in inverse relation to the ambient temperature. The system may otherwise control lighting fittings by way of dimming ballasts, and may also include person-detectors, timers etc.

WO 2005/015519 A1



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.